

# KODAK Portrait 3D Printer



## RELIABILITY IN ENGINEERING MATERIALS

Only a fully enclosed environment with all-steel components and a lifting dual-extrusion system can ensure a good performance when using high temperature polymers.



UP TO 4 YEARS WARRANTY\*  
**\$3499**



### Ease of use

An intuitive touchscreen, automatic leveling and calibration and preset print parameters for every material will help you optimize the design-to-print process and keep the focus on your work.



### A professional 3D printing platform

Experience free access to the KODAK 3D Cloud, an IT-compliant printer management software powered by 3DPrinterOS.



### Variety of high-quality materials

From flexibles to nylons, our low moisture, high dimensional accuracy filaments complement the hardware and software to serve your different applications.

\* A limited one (1) year Warranty is included, extendable up to three (3) additional years at a cost to cover annual service check-ups

# KODAK Portrait 3D Printer



## It's safe

For usage in offices or educational institutions, the enclosed chamber with air filtration prevents toxic particles or unwanted odors from coming out of the printer, while keeping fingers away from hot moving parts.



## It's solid

A stable all-steel structure in an enclosed environment capable of monitoring temperature accounts for a repeatable 3D printing experience.



## It's connected

Access our management platform via Wi-Fi or the LAN port to slice online, monitor your prints, run a print farm and receive over-the-air updates, among other functionalities.



## It's versatile

Our dual extrusion with automatic nozzle lifting includes swappable PTFE or all-metal hotends for optimal performance with each material.

## Supported materials



ABS



Flex 98



HIPS



Nylon 6



Nylon 12



PLA +



PLA Tough

Coming soon:  
PETG and PVA

Compatible with  
third-party materials

## Specifications

Build volume - single extrusion	215 x 210 x 235 mm (8.5x 8.3 x 9.3")
Build volume - dual extrusion	170 x 210 x 235 mm (6.7 x 8.3 x 9.3")
Print head	Dual extrusion with automatic nozzle lifting
Hotend material	1 all-metal, 1 PTFE, swappable
Build plate	Glass attached by magnets
Bed leveling	Automatic
Air filtration	HEPA filter and activated carbon
Layer resolution	0.4mm nozzle: 20 - 250 micron
Display	5" color screen, multiple languages
Connectivity	Wi-Fi, LAN, USB drive
Monitoring	Live camera
Light signals	Indicate printer status
Supplied software	KODAK 3D Cloud, KODAK 3D Slicer
Accessories	2 filament cases, toolkit

[www.kodak.com/go/3Dprinting](http://www.kodak.com/go/3Dprinting)

The KODAK trademark, logo and trade dress are used under license from Eastman Kodak Company.

